

PL-14000



Parking Lifts

14,000-lb. Capacity / Three-Level Parking Lift / Platforms

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

Triple the Capacity of a Typical Parking Area

BendPak's PL-14000 [parking lift](#) is designed for indoor or outdoor operation and is the most cost-effective way to triple the capacity of parking areas. Each three-stacker model is the ultimate space saver, allowing three vehicles to be stacked in a single parking space. With multiple frame dimensions and closeout leg options to choose from, the perfect three-level auto stacker is incredibly durable and smooth-running. It's built to last for years without heavy maintenance.

Features

- 7,000-lb. capacity per deck / 14,000-lb. capacity total
- Perfect for cars, light trucks, motorcycles and ATVs
- Rugged I-beam and C-channel construction
- Built-in wheel stops
- Wide base-plate for maximum stability
- Front and rear wheel chocks
- Two-position fail-safe locking system
- Superstructure features durable powder-coat finish
- Single hydraulic cylinder with heavy-duty steel lifting cable
- Heavy-duty steel construction
- Reliable electric-hydraulic power system
- Full-width platform to keep bottom vehicles protected
- Simple controls
- Oversized sheave diameter reduces cable fatigue
- High-speed lifting
- Heavy-duty 3/8" aircraft cable and 1.25" roller axles
- Multi-position safety locks in each column
- Adjustable lock ladders
- Runways feature non-skid surface
- Push-button pneumatic safety release
- Independent backup slack-cable safety latches
- Inside runways adjust for different tread widths
- Customizable power unit location



Specifications

Lifting Capacity	14,000 lbs. (6,350 kg)
Overall Width	119" (3,023 mm)
Overall Length	194" (4,931 mm)
Overall Height	280.3" (7,121 mm)
Platform Length	137" (3,480 mm)
Upper Platform Spacing	96.5" (2,451 mm)
Middle Platform Spacing	75.5" (1,921 mm)
Bottom Spacing	82.5" (2,100 mm)
Drive-Thru Clearance	91" (2,316 mm)
Lifting Time	145 sec
Voltages	208-230V, 380V or 440V

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.