

PL-18000



Parking Lifts

18,000-lb. Capacity / Four-Level Parking Lift / Platforms

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

Four Times the Charm

The quad-stacker PL-18000 [parking lift](#) allows four vehicles to be stacked in a single parking space. Shared, ganged columns reduce the number of components (as well as the cost) required for multi-unit installations. The base frame on this parking lift is made to distribute the load throughout the entire structure for maximum safety and usability on virtually any concrete floor.

Features

- 6,000 lb. capacity per deck / 18,000 lb. capacity total
- Superstructure features durable powder-coat finish
- Perfect for cars, light trucks, motorcycles and ATV's
- Rugged I-beam and C-channel construction
- Single hydraulic cylinder with heavy-duty steel lifting cable
- Built-in wheel stops
- Heavy-duty steel construction
- Wide base-plate for maximum stability
- Reliable electric-hydraulic power system
- Front and rear wheel chocks
- Full-width platform to keep bottom vehicles protected
- Two-position fail safe locking system

Specifications

Lifting Capacity 18,000 lbs. (8,164 kg)

Ramp Locking Positions 3

Lock Spacing 80" (2,032 mm)

Lifting Time 210 sec

Overall Width 119" (3,023 mm)

Overall Length 194" (4,931 mm)

Overall Height 360" (9,144 mm)

Upper Platform Spacing 98" (2,493 mm)

Second Platform Spacing 76" (1,933 mm)

First Platform Spacing 77" (1,954 mm)

Floor Level Spacing 78.5" (1,994 mm)

Drive-Thru-Clearance 91" (2,316 mm)

Voltages 208-230V, 380V or 440V



Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.