

PL-6KT

Parking Lifts

SKU# 5175154

18,000-lb. Cap Parking Lift / Triple / Independent Platforms

Questions? Contact BendPak's Sales Team


sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

The Sexiest Vehicle Stacker Money Can Buy

The PL-6KT triple-wide [parking lift](#) is one of the most efficient parking units ever designed. The key to its design is a streamlined, four-column structure that leaves all three lifting platforms free from surrounding posts, making it safer and easier to enter and exit parked vehicles.

This parking lift is equally useful in large residential garages and commercial spaces. Municipal parking lots and custom shops looking for extra parking don't need to waste money buying multiple lifts that may or may not even fit in their space. A triple-wide lift is the most efficient way to turn three parking spots into six.



Features

- 6,000-lb. capacity per deck
- Perfect for cars, light trucks, motorcycles and ATVs
- Rugged I-beam and C-channel construction
- Built-in wheel stops
- Wide base-plate for maximum stability
- Front and rear wheel chocks
- Superstructure features durable powder-coat finish
- Dual hydraulic cylinders with heavy-duty steel lifting cable
- Heavy-duty steel construction
- Reliable electric-hydraulic power system
- Full-width platform to keep bottom vehicles protected
- Simple controls
- Oversized sheave diameter reduces cable fatigue
- High-speed lifting
- Features heavy-duty 3/8" aircraft cable
- Rugged 1.25" roller axles
- Multi-position safety locks in each column
- Runways feature non-skid surface
- Push-button pneumatic safety release
- Independent backup slack-cable safety latches
- Customizable power unit location

Specifications

Lifting Capacity	6,000 lbs. (2,722 kg)
Overall Width	308" (7,834 mm)
Overall Length	236.5" (6,008 mm)
Overall Height	123.75" (3,140 mm)
Min. Runway Height	9" (230 mm)
Max. Rise	89" (2,261 mm)
Width Between Posts	283" (7,197 mm)
Platform Width	82" (2,086 mm)
Platform Length	152" (3,862 mm)
Drive-thru Clearance	93" (2,374 mm)
Locking Positions	1 / Adjustable
Lifting Time	30 sec
Standard Motor	220 VAC / 60 Hz / 1Ph

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.