

PLT-6S



Parking Lifts

SKU# 5175220

6,000-lb. Capacity / Platform Parking Lift

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

Your Future Favorite Lift

BendPak's PLT-6S [parking lift](#) was designed for both commercial and residential use and is the perfect car parking solution when ceiling clearances are limited and vehicle heights are restricted. Each PLT-6S parking lift features dual hydraulic lifting cylinders a high-strength safety lock system.

Features

- 6,000-lb. lifting capacity
- Accommodates cars and small SUVs
- Heavy steel locks automatically engage at full-rise
- Manually operated lock release
- Dual hydraulic lifting cylinders
- Cantilevered design with lateral torsion bar
- No chains or cables
- Individual, or single multi-unit power unit configurations
- For commercial or residential applications
- Manually operated lock release
- Hydraulic safety valves (velocity fuses)
- Available in 110V or commercial 220V power options



Specifications

Lifting Capacity 7,000 lbs. (3,175 kg)

Overall Width 98.3" (2,497 mm)

Overall Length 153.5" (3,899 mm)

Overall Height 74" (1,880 mm)

Platform Width 79.1" (2,010 mm)

Platform Length 134.9" (3,427 mm)

Platform Rise 50.6" (1,286 mm)

Ramp Rise 62.9" (1,599 mm)

Leg Length 98.8" (2,509 mm)

Lifting Time 55 sec

Standard Motor 220 VAC / 60 Hz / 1Ph

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.

Multi-station power unit and special voltages available upon request.