

R980XR



Tire Changer

SKU# 5140146

Swing Arm, 30" Capacity, 220V, 1-Phase, 50/60hz

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Designed to Perform and Built to Last

The Ranger R980XR [tire changer](#) features variable high-speed modes that perform masterfully on a wide variety of wheels, including virtually all OEM configurations and performance tire-and-wheel configurations.

Each R980XR tire changer features the latest in design and wheel service technology, providing the best value and performance in its class. The powerful motor and gearbox work systematically at a controlled speed for easy tire removal and installation. Ergonomic controls are sensibly placed to minimize excessive reaching, walking or bending, resulting in more jobs per day and increased profits. Large storage trays provide ample space for accessories.

Specifications

Motor	3 HP (220 VAC 50-60 HZ)
Drive System Type	Electric / Air
Air Requirement	140-165 PSI (10-11 BAR)
Wheel Clamping Method	4 Clamps - Internal / External
Table Clamping System	Dual Pneumatic Cylinders
Bead Breaking System	Pneumatic Blade / Dual
Tower Design	Rigid / Fixed
Power Assist Towers	N/A
Bead Seating System	Turbo Blast / Bead Seating
Internal Rim Clamping Capacity	10" - 30" (254 mm - 762 mm)
External Rim Clamping Capacity	9" - 28" (229 mm - 711 mm)
Turntable Tire Width Capacity (Mounting)	4" - 18" (102 mm - 457 mm)
Bead Breaker Tire Width Capacity (Demounting)	1.5" - 13" (38 mm - 330 mm)
Maximum Tire Diameter	50" (1,270 mm)
Shipping Weight	800 lbs. (363 kg)



Standard Features

- Inflation Gauge With Integrated Air Dump Valve
- Inflation Pressure Regulator/Limiter
- Brush
- Alloy-Steel Mount/ Demount Head
- Plastic-Polymer Mount/Demount Head
- Oiler / Lubricator
- Air Regulator
- Breaker Bar
- Large Soap / Lubricator Bucket