

# XPR-18CL



## Two-Post Lifts

SKU# 5175409

18,000-lb. Capacity, Clearfloor, Standard Arms

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

## The Beast with Two Posts

Shops that work on massive fleets and vehicles need a powerful car lift with a small footprint, so only BendPak's 18,000-lb. capacity XPR-18CL will get the job done safely and efficiently. It offers the most lifting capacity of any two-post lift we make, which means you get the best column, carriage and frame component construction we offer.

With an XPR-18CL [two-post car lift](#), you will service an incredibly diverse array of vehicles. High-capacity two-post lifts are commonly known as "all-service" lifts. Given their versatility, they're the most common lift type found in professional shops. And, because they're going to be in so many shops, it's important that the XPR-18CL can lift any vehicle that falls well under the max weight capacity.



## Optional Extended Height

SKU# 5175411

XPR-18CL-192

192" Overall Height

## Features

- 18,000-lb. lifting capacity
- Padded overhead safety shutoff bar
- Extended height top-beam provides greater clearance
- Single-point safety release
- Dual direct-drive hydraulic cylinders
- Dual-synchro equalization system for equal lifting
- Oversized 53" tall carriage for superior strength
- Electric / hydraulic power system
- Oversized A36 steel base plates
- Self-lubricating dura-glide UHMW polyethylene bearings
- Safety locks in each column spaced every 3"
- Automatic arm restraints
- Heavy-duty 1/2" aircraft-quality equalizer cables
- Oversized cable sheave diameter reduces cable fatigue
- Durable, rubber lift pads with stackable adapters
- Multi-piece adapter set includes four 6" stackable adapters, four 3" stackable adapters, four polyurethane contact pads and four frame cradle pads. Ideal for trucks and vans with running boards or auxiliary fuel tanks.
- Convenient storage is included for truck and van adapters
- Versatile drop-in contact pads with stackable adapters

### Quality Assurance for Heavy-Duty Lifting

When you buy BendPak, you can expect a significant boost in performance and lift operation life expectancy because your lift is built to be the last one you ever purchase. No one surpasses us in quality and safety. That's why when you get one of our lifts, you get more than just a great product. You get peace of mind. That's the benefit of owning a BendPak.

### Triple-telescoping arm set

Three-stage front and three-stage rear arms provide greater maximum reach, as well as superior minimum retraction. Use this super-duty lift system for raising standard passenger vehicles and heavy-duty trucks.

### Optional column extension

BendPak can increase your overhead clearance to maximize the number vehicle types you can service in this weight class.

### High-speed hydraulics

Free-flow, high-pressure 3/8" hydraulic lines, a high-flow pump and integrated AC power-unit increase ascent and descent speeds for enhanced productivity.

### Extended Height

The safe and rugged XPR-15C-192 two-post lift features extended height columns for added overhead clearance, as well as an adjustable top beam to accommodate wide or narrow installation setups.

\*Optional bolt-on height extension available.

# Specifications

Model	XPR-12CL	XPR-15CL	XPR-18CL
SKU#	5175405	5175408	5175409
Lifting Capacity	12,000 lbs. (5,443 kg)	15,000 lbs. (6,804 kg)	18,000 lbs. (8,165 kg)
<b>A - Rise</b>	69" (1,753 mm)	69" (1,753 mm)	69" (1,753 mm)
<b>B - Rise + Pad Only</b>	74" (1,880 mm)	74" (1,880 mm)	74" (1,880 mm)
<b>C - Max. Lifting Height</b>	80" (2,032 mm)	80" (2,032 mm)	80" (2,032 mm)
<b>D - Min. Height + Pad</b>	5" (127 mm)	5" (127 mm)	5" (127 mm)
<b>E - Height Overall (*)</b>	170" (4,318 mm)	170" (4,318 mm)	170" (4,318 mm)
<b>F - Width Overall</b>	155" (3,937 mm)	155" (3,937 mm)	155" (3,937 mm)
<b>G - Outside Columns</b>	144" (3,658 mm)	144" (3,658 mm)	144" (3,658 mm)
<b>H - Inside Columns</b>	120" (3,048 mm)	120" (3,048 mm)	120" (3,048 mm)
<b>I - Drive-Thru Clearance</b>	106" (2,692 mm)	106" (2,692 mm)	106" (2,692 mm)
<b>J - Floor to Top Switch (*)</b>	165" (4,191 mm)	165" (4,191 mm)	165" (4,191 mm)
<b>K - Front Arm Reach (MAX)</b>	32" (813 mm)	39" (991 mm)	39" (991 mm)
<b>K - Front Arm Reach (MIN)</b>	60" (1,524 mm)	60" (1,524 mm)	60" (1,524 mm)
<b>L - Rear Arm Reach (MAX)</b>	32" (813 mm)	39" (991 mm)	39" (991 mm)
<b>L - Rear Arm Reach (MIN)</b>	60" (1,524 mm)	60" (1,524 mm)	60" (1,524 mm)
<b>Screw Pad Adjustment</b>	Not Compatible	Not Compatible	Not Compatible
<b>Max. Load per Arm</b>	3,000 lbs. (1,361 kg)	3,750 lbs. (1,701 kg)	4,500 lbs. (2,041 kg)
<b>Time to Full Rise</b>	45 seconds	45 seconds	45 seconds
<b>Noise</b>	45 dB	45 dB	45 dB
<b>Motor</b>	220 VAC / 60 Hz / 1 Ph	220 VAC / 60 Hz / 1 Ph	220 VAC / 60 Hz / 1 Ph

\*Optional bolt-on top extension for columns raises the overall height and overhead safety bar an additional 24". Must be ordered from BendPak at time of order.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult [www.autolift.org](http://www.autolift.org) for a complete list or contact BendPak via [contact@bendpak.com](mailto:contact@bendpak.com).

